

MATERIAL SAFETY DATA SHEET

1 PRODUCT INFORMATION

- PRODUCT NAME : "VITRIUM" CLEAR PROTECTANT SEALANT
Coating Material in liquid type

2 COMPANY IDENTIFICATION

- NAME OF MANUFACTURER : AIBON SANGYO PTY. LTD
- ADDRESS : 3-11-5 MIYOSHI, KOTO-KU, TOKYO, JAPAN
- NAME OF EDITOR : YASUO TSUGE
- TELEPHONE NUMBER : 03-562-1620
- FAX NUMBER : 03-5620-1621
- PRINT DATE : Apr 17, 2009

3 USES FOR PRODUCT : HANDY CRAFT & HOBBY

4 CLASSIFICATION OF HAZARD 1

- CLASSIFICATION NAME : NOT RELEVANT TO THE CLASSIFICATION STANDARD.

5 CHEMICAL IDENTIFICATION

- SUBSTANCE / MIXTURE : MIXTURE
- CHEMICAL NAME : SYNTHETIC RESIN COATING LIQUID
- COMPONENT & CONTENT

NAME	CONTENT (%)	CAS NO.
WATER-SOLUBLE ACRYLIC EMULSION	45	
MOISTURE AND THE LIKE	55	

6 CLASSIFICATION OF HAZARD 2

- ADVERSE HUMAN HEALTH EFFECTS : IN CASE OF NORMAL HANDLING, TOXICITY AND IRRITANT PROPERTIES ARE CONSIDERED TO BE LOW.
BUT, IT IS POSSIBLE TO OCCUR COMPARATIVE SLIGHT IRRITANT TO EYES, RESPIRATION ORGAN SKIN AND MUCOUS MEMBRANE.

7 HANDLING RECOMMENDATIONS AND MARK

- HANDLING : HANDLE THE PRODUCT AT A PLACE WITH GOOD VENTILATION.
PRODUCT IS INEDIBLE. DO NOT EAT NOR DRINK.

- MARK



8 SAFETY RECOMMENDATION : BEFORE USING PRODUCT, READ WELL HANDLING MANUAL AND MUST FOLLOW IT.

WHEN LEAKING OUT FROM THE CONTAINER, IT IS RECOMMENDABLE TO WIPE OFF BY PAPERS, CLOTHES AND SO ON, OR TO CLEAN UP BY THE LARGE AMOUNT OF WATER, HOWEVER, BE NOTED THAT THICK LIQUID SHOULD NOT BE DISCHARGED INTO THE RIVER.

9 FAST AID TREATMENT

- IN CASE OF SWALLOWING BY FAULT : RINSE THE INSIDE OF MOUTH WELL AND CONSULT WITH THE DOCTOR IMMEDIATELY. DON'T SWALLOW THE VOMITS.
- IN CASE OF SKIN CONTACT WHEN FEELING IRRITATION OR HAVING A RASH, CONSULT WITH THE DOCTOR IMMEDIATELY.
- WHEN GETTING IN EYE WHEN IT GETS IN EYES, RINSE IT OUT OF EYES WITH WATER AT LEAST 15 TO 20 MINUTES RECOMMENDABLE AND CONSULT WITH THE DOCTOR IMMEDIATELY.

10 STORAGE RECOMMENDATION : STORE THE PRODUCT IN A ROOM TO PREVENT FREEZING AND DIRECT SUNLIGHT, WITH THE TEMPERATURE AROUND 5 TO 30°C WELL VENTILATED, AND TIGHTLY CLOSE THE CONTAINER AFTER USE.

11 PHYSICAL AND CHEMICAL PROPERTIES : PRODUCT IS HIGH VISCOSITY LIQUID PROPERTIES AND BECOMES A SOLID WHEN DRYING.

12 STABILITY AND REACTIVITY

- STABILITY : STABLE IN NORMAL CONDITION
 - REACTIVITY : STABLE IN NORMAL CONDITION
- QUALITY WARRANTY IS WITHIN 10 TO 12 MONTHS AFTER PRODUCTION DATE WITHOUT OPENING AND WITHOUT USE.

13 NOTICE ON DISPOSAL : WHEN DISCARDING, FOLLOW THE INDUSTRIAL WASTE DISPOSAL AND CLEANING LAW. DON'T THROW IT AWAY INTO THE RIVER.

14 TRANSPORT INFORMATION

- INTERNATIONAL AGREEMENT : NOT APPLICABLE.

15 OTHERS : *THE CONTENTS OF THIS DATASHEET ARE BASED ON REFERENCES AND INFORMATION AVAILABLE AS OF THE PRESENT. HOWEVER, THE DATA AND EVALUATION DESCRIBED HERE ARE PREPARED FOR THE PURPOSE OF THE PRESENTATION OF INFORMATION BUT NOT FOR THE PURPOSE OF ANY GUARANTEE.

*SINCE THE DESCRIBED CONTENTS ARE BASED ON CONCEIVABLE NORMAL CONDITIONS, IN THE CASE OF SPECIAL HANDLING, PLEASE APPLY SAFETY MEASURES SUITABLE FOR NEW PURPOSE AND USAGE.